

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification System for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

EX COMPONENT CERTIFICATE

Certificate No.: **IECEx BAS 10.0005U** Page 1 of 4

Issue 3 (2017-11-29) Issue No: 4 Status: Current Issue 2 (2014-01-16) Issue 1 (2012-03-01) Issue 0 (2010-04-09)

2024-03-26 Date of Issue:

Applicant: **Eaton Electric Limited**

Great Marlings Butterfield Luton Bedfordshire LU2 8DL

United Kingdom

Ex Component: 9376-SP Trunk Surge Protector

This component is NOT intended to be used alone and requires additional consideration when incorporated into other equipment or systems for use in explosive atmospheres (refer to IEC 60079-0).

D Brearley

Type of Protection: Flameproof, Increased Safety, Encapsulation

Marking: Ex db eb mb IIC Gb (-40°C ≤ Ta ≤ +75°C)

Approved for issue on behalf of the IECEx

Certification Body:

Certification Consultant Position:

Signature:

(for printed version)

(for printed version) 26/3/2024

This certificate and schedule may only be reproduced in full.

This certificate is not transferable and remains the property of the issuing body.

The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate history:

Certificate issued by:

SGS UK Limited Rockhead Business Park Staden Lane **Buxton, Derbyshire SK17 9RZ United Kingdom**





IECEx Certificate of Conformity

Certificate No.: **IECEx BAS 10.0005U** Page 2 of 4

Date of issue: 2024-03-26 Issue No: 4

Manufacturer: **Eaton Electric Limited**

> **Great Marlings** Butterfield Luton Bedfordshire LU2 8DL

United Kingdom

Manufacturing locations:

Eaton Electric Limited Great Marlings Butterfield

Luton Bedfordshire LU2 8DL **United Kingdom** **MTL Instruments Pvt Limited** No 3 Old Mahabalipuram Road

Sholinganallur Chennai 600119

India

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The component and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

Edition:4.1

IEC 60079-1:2014 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"

Edition:7.0

IEC 60079-18:2017 Explosive atmospheres - Part 18: Protection by encapsulation "m"

IEC 60079-7:2017 Edition:5.1

Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the component listed has successfully met the examination and test requirements as recorded in:

Test Reports:

GB/BAS/ExTR09.0125/00 GB/BAS/ExTR11.0194/00 GB/BAS/ExTR13.0147/00 GB/BAS/ExTR16.0297/00 GB/SGS/ExTR24.0037/00

Quality Assessment Reports:

GB/BAS/QAR06.0022/11 GB/BAS/QAR07.0017/10



IECEx Certificate of Conformity

Certificate No.: IECEx BAS 10.0005U Page 3 of 4

Date of issue: 2024-03-26 Issue No: 4

Ex Component(s) covered by this certificate is described below:

The 9376-SP Trunk Surge Protector is a component module that is designed to connect across a Fieldbus line as part of other equipment. It comprises an encapsulated circuit and live disconnect connectors to enable it to be fitted and removed without first powering down the Fieldbus line. Its function is to provide transient protection for other equipment connected to the Fieldbus line.

SCHEDULE OF LIMITATIONS:

- 1. The 9376-SP Trunk Surge Protector must be housed in an appropriately certified Ex e enclosure.
- 2. The 9376-SP Trunk Surge Protector must plug into equipment that uses the socket part of the connector covered by certificate IECEx BVS 19.0026U.
- 3. Due to the presence of transient protection components between the fieldbus and earth connections, the 9376-SP Trunk Surge Protector will not withstand a 500V a.c. dielectric strength test. This must be taken into account during installation.
- 4. The ambient temperature must not exceed +75°C.
- 5. The 9376-SP Trunk Surge Protector shall only be powered from supplies conforming to IEC 61158.
- 6. The 9376-SP Trunk Surge Protector shall only be connected into equipment that causes the secondary latching connector to limit movement before the live-demateable connector plug and socket metal parts separate by over 1.9mm.
- 7. When used within the limitations present on this certificate, the component is intended to meet the requirements for temperature class T4 without further temperature testing.



IECEx Certificate of Conformity

Certificate No.: IECEx BAS 10.0005U Page 4 of 4

Date of issue: 2024-03-26 Issue No: 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Variation 4.1

To confirm compliance with the requirements of IEC 60079-0: 2017 Ed.7, IEC 60079-1: 2014 Ed. 7, IEC 60079-18: 2015+A1:2017 Ed.4.1 and IEC 60079-7: 2015+A1:2017 Ed.5.1

Variation 4.2

To permit a change of certificate for the "db eb" connector to IECEx BVS 19.0026U

Variation 4.3

Updated label marking to show "db eb" instead of "d e".

EXTR: GB/SGS/ExTR24.0037/00 File Reference: 24/0086